

PITTSBURGH CORNING

FOAMGLAS®

INSULATION ACCESSORIES

800 Presque Isle Drive
Pittsburgh, Pennsylvania 15239-2799
Tel: 724/327-6100 Fax: 724/327-5890
www.foamglasinsulation.com

PITWRAP® SS PRIMER

PRODUCT DATA SHEET

IMPORTANT: MATERIAL SAFETY DATA SHEETS ARE AVAILABLE AND SHOULD BE READ BEFORE USING THIS PRODUCT.

DESCRIPTION:

PITWRAP® SS Primer is specially formulated to promote adhesion of PITWRAP® self-sealing jacketing when the laps are slightly dusty or the application is below 50°F (10°C).

TYPICAL PROPERTIES:

Color:	Translucent
	White
Appearance:	Thin liquid
Solids, %wt:	21
Wt/gallon, lbs. (kg/l):	7.7 (0.92)
Coverage, ft ² /qt: (m ² /l)	75 (7.4)
Application Temperature, °F, (°C):	20 to 100 (-7 to 38)
Flammability: Wet:	Flammable
Dry:	Combustible
Flash Point, closed cup, °F, (°C):	40 (4)
Solvent:	Toluene

*Properties subject to change. Consult Pittsburgh Corning Corporation

MATERIAL PREPARATION:

Stir well before using. Keep container closed when not in use. See Caution Statement.

APPLICATION INSTRUCTIONS:

Apply a thin coat of primer to the bituminous side of the jacketing lap with a brush or swab. Allow the solvent to evaporate for a few minutes before seal is made. Press lap and roll completed joint with a hard roller such as a wallpaper seam roller. Check for unsealed areas along the seam and repress or reseal before back filling. See one of the PITWRAP® self-sealing jacketing product data sheets (FI-179A), (FI-234), or (FI-235) for details of jacketing application.

LIMITATIONS:

PITWRAP® SS Primer is not a gap-filling sealant. It is used only to assist in making a bond. Keep lap area free of dust and dirt.
Use primer on jacketing only when necessary because of dust or application temperature below 50°F (10°C).
Use only on the bituminous side of the jacketing.
Solvent may attack organic foams.

FIRE HAZARD CLASSIFICATION:

- Health: 3 Fire: 3 Reactivity: 0

PACKAGING:

1 quart container

CAUTION:

This material is intended to be used only with FOAMGLAS® insulation and PITWRAP® self-sealing jacketings and in conformity with Pittsburgh Corning's standard instructions.

Be sure you have read and understood all instructions and Material Safety Data Sheets before using.
Use only with adequate ventilation and with protection equipment given on the MSDS.

INGREDIENTS:

Toluene

CAS #

108-88-3

IRRITANT:

Contains 76% by weight toluene (CAS #108-88-3). Mildly toxic by inhalation. Solvent and vapors are irritating to eyes, skin and respiratory tract. Avoid breathing vapors or contact with skin. Use only in well ventilated areas.

HARMFUL OR FATAL IF SWALLOWED

FLAMMABLE:

Keep away from open flame and other ignition sources. Keep container closed when not in use.

If spilled on clothing remove promptly avoiding ignition sources. Vapor may travel a distance to ignition sources. Store in areas of flammable liquid.

KEEP OUT OF REACH OF CHILDREN.

The information contained herein is accurate and reliable to the best of our knowledge. But, because Pittsburgh Corning Corporation has no control over installation workmanship, accessory materials or conditions of application, **NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, IS MADE** as to the performance of an *installation* containing Pittsburgh Corning Products. In no event shall Pittsburgh Corning be liable for any damages arising because of product failure, whether incidental, special, consequential or punitive, regardless of the theory of liability upon which any such damages are claimed. Pittsburgh Corning Corporation provides written warranties for many of its products, and such warranties take precedence over the statements contained here

PITWRAP® SS Primer
FI-155 Rev. 02/2005
Replaces Rev 12/99